



Board of County Commissioners

P O Box 608
Dove Creek, CO 81324

Phone: (970) 677 2383 Fax: (970) 677-2815

Email Address: dcdolocnty@fone.net

ROAD SPECIFICATIONS CONTROL OF WORK AUTHORITY OF THE COUNTY ROAD SUPERVISOR

The County Road Supervisor will decide all questions which may arise as to the quality and acceptability of materials furnished and work performed; all questions which may arise as to the interpretations of plans and specifications and all questions as to the acceptability of any phase of work on those projects proposed for acceptance into Dolores county Road System.

A. RIGHT OF WAY

1. Minimum of sixty (60) feet unless otherwise varied by the Board of County Commissioners.
2. All right of ways shall be cleared of trees, brush and trash.

B. ROAD BED CONSTRUCTION

1. Culverts shall be placed at all natural and manmade drainages.
2. Minimum size shall be fifteen (15) inches diameter.
3. The top of the culvert shall be a minimum of one (1) foot below the finished base course grade.

C. SUBBASE COURSE- Sandrock

1. Pit run or 4" minus of a minimum 6" compacted.
2. Top 2" will be grid rolled down to a 1" minus material to facilitate grading.
3. Running surface of road will be a minimum of 22" when completed with base rock. Road edge to bottom of ditch shall be a 3:1 slope, back slope 2:1 maximum.

D. UTILITIES

When utility type devices are to be installed within the County Road right-of-way, the County policy on Utility Use of County Right-of Ways shall apply.

E. TRAFFIC CONTROL

1. Approved barricades, warning signs and flagman when required shall be used in

- connection with all road work.
2. Road designations and traffic control signs as required by the County Road Supervisor shall be installed in an approved manner prior to acceptance of the road.

F. GUARANTEES

All road construction performed by the contractors and/or developers to be accepted into the County Road System shall be guaranteed for a minimum of one year to meet the continual standards to which it was constructed. Such guarantee may be by bond, cash deposit, pledged securities, or other valuable considerations acceptable by the Board of County Commissioners.

G. STRUCTURES AND/OR FENCES

Any private structures, including fences, etc. shall be installed at a minimum of thirty (30) feet from the center of the existing County Road.

H. MAILBOXES

Upright mailbox post must be 6ft. from the edge of the driving surface. Mailbox opening must be at least 18 inches back from the driving surface and mailbox/mailbox platform must sit at least 42 inches above the level of the driving surface.

I. AMENDMENTS

The Board of County Commissioners may from time to time amend these regulations.